

Perfectly compatible system components quickly on-site and ready for use

READY TO BUILD

Maximum customer orientation and best consultation. With the new service concept "Ready to Build" the customer gets the perfectly compatible system components just in time. No matter whether granules or polyurethane, whether for athletic tracks, playgrounds or stage building: single-source delivery from Melos - at a good price!







System One and Two Layer



Artificial Turf





Spray Coating System Type A



Two Layer System Type B



One Layer EPDM System

Type C



Sandwich System

Type D




Full Pour System Type E



Acrylics

CHOOSE THE DESIRED SYSTEM.

GET THE RIGHT PRODUCTS FROM US.











Recycled Granules Polyurethane / Epoxy



Durable

Weatherproof

Flame-retardant

28 standard colours

Reasonable in care

Virgin material

Eco-friendly

Freedom to be creative

COLOURED GRANULES

Motivation for sports and enjoyment of leisure – we have many good reasons for manufacturing granules in the most attractive colours. As a leading manufacturer in the field of coloured rubber granules for bound floor covering systems we are committed to offer the highest quality and the widest possible range of colours. In addition to our range of 28 standard colours, we will be glad to create individual special colours on request for unique and representative designs both indoors and out.

All colours supplied by us have a high colour stability – for a long-lasting use of your sports and leisure floorings.





Grain size 0.0 - 0.5 | 0.5 - 1.5 | 1.0 - 2.0 | 1.0 - 2.5 and 1.0 - 3.5 mm

The worldwide used standard product for diverse outdoor floor applications and PUR system solutions has established itself with all building companies in the course of the decades primarily with the grain size 1.0 - 3.5 mm. Avail yourself of the security provided by the UV-resistant and elastic granules in their great colour variety.

Wide range of colours - 28 standard colours and a variety of special colours, such as Brilliant Red

Wide range of Colour Blends – Easy Blend Pure, Colour Blend or other Blends with a special colour – e.g. Amazing Africa and Fairy Flowers

» Product information

Property	Unit	Value*	Test standards
Density	g/cm ³	1.60	DIN EN ISO 1183-1
Polymer content	%	approx. 20	
Bulk density (± 10 %)	g/l	650	DIN EN ISO 60
Hardness	Shore A	60	DIN ISO 48-4
Tensile strength	MPa	> 6	DIN 53504
Elongation at break	%	> 700	DIN 53504
Grain size	mm	0.0 - 0.5 0.5 - 1.5 1.0 - 2.0 1.0 - 2.5 und 1.0 - 3.5 (other grain sizes on request)	
Polymer base	EPDM		
Flame retardance	Flame-retardant material compliant with class $c_{\rm fl}$ -s1 (DIN EN 13501-1) available		


» Environmental and health tests

EN 71-3	Fulfils the requirements of the toy safety standard with respect to the migration of certain elements.
PAH (REACH)	Fulfils the requirements of regulation (EC) No. 1907/2006, Annex XVII, entry 28 and 50.

- * Technically related variations in property and colour and productionrelated variations as well as innovations and technical changes are reserved. Products shown may differ in configuration from the actual
- ¹ The RAL colour specifications are nonbinding approximations. Differences in colour of the images are due to printing process.

» Available colours

RAL Approx. value1



Rainhow Green Code: 46 5600 RAL: 6025 Signal Green Code: 46 4600

RAL: 6032 Iron Grey Code: 69 0800

RAL: 7011 Slate Grey

Code: 46 3100 RAL: 7015

Light Grey Code: 46 3800 RAL: 7035

Brown Code: 46 2800 RAI - 8024

Black Code: 46 3900 RAL: 9004



EPDM MULCH

Grain size 2.0 - 30.0 mm

EPDM Mulch is 100 % dyed, meaning it retains its colour and is kind to the environment. EPDM Mulch is a durable, colour-fast alternative to surface-coated rubber mulches made from recycled tyres.

As a water-permeable surface Melos® EPDM Mulch provides a hygienic and economic alternative to organic mulches. A smooth and poured in place EPDM Mulch surface enables barrier-free and safe playing fun.

DECO GRANULES

Grain size 1.0 - 3.5 mm

A shimmering water feature, multifaceted landscapes, luminous meadow scenery or dynamic fire images – Melos® Deco Granules provide stage and set designers with numerous possibilities for creating realistic and imaginative stage designs. Melos® Rubber Granules provide a safe and practical alternative to familiar theatre stage decorations, such as highly combustible cork or coarse and dusty sand.



Flame-retardant

INFILL GRANULES

INFILL EPDM ST

Grain size 0.5 - 1.5 | 0.5 - 2.0 mm | **Bulk density** 650 g/l

Tested and flexible: The proven Infill EPDM ST is very lightfast and weatherproof. Many years of experience with infill granules have shown that this crosslinking method results in a product with solid ageing stability and optimal sports-technical attributes. The selection of suitable pigments ensures the durability of the colours. This optimum product is based on high-grade materials. Tested and flexible: The proven Infill EPDM ST is very lightfast and weatherproof.



Sports-functiona











BASE LAYER PRODUCTS

MELOS® CUSHION+

Grain size 2.0 - 30.0 mm

Melos® Cushion+ is a high-quality system component for the base layer in athletics and multisport surfaces. The special feature: Melos® Cushion+ consists of 100 % EPDM virgin material! Due to the fibrous material form, the best fall protection properties are achieved – with an optimized material consumption. Melos® Cushion+ is manufactured from high-quality raw materials, is 100 % REACH-compliant and is highly water-permeable for ideal durability. All requirements for contemporary fall protection are met. The product features pay off for the client, give parents a safe feeling and are simply fun for children.

INFINERGY **D-BASF** Infinergy

Infinergy is a high-quality component for the base layer in fall protection surfaces. Infinergy used in the base layer is elastic like rubber, but lighter. The closed-cell particle foam combines low weight with high continuous load-bearing capacity. Perfect for sports, leisure and many other applications.

MELOS® EPDM SOFT

Grain size 0.5 - 1.5 | 1.0 - 4.0 | 1.0 - 6.0 mm

Melos® EPDM Soft is a newly developed system component for the base layer in artificial turf pitches, athletics and multisport surfaces. The Melos® EPDM Soft used in the base layer is manufactured from high-quality EPDM virgin material and is therefore 100 % REACH-compliant. The manufacturing process and the formulation of the Melos® EPDM Soft granules guarantee the highest sports functional properties such as optimal force reduction and vertical deformation.

100 % virgin material

Base layer products are manufactured from high-quality EPDM virgin material and are therefore 100% REACH-compliant (REACH-Regulation Annex XVII, Entry 28 and 50).

RECYCLED GRANULES

Grain size 1.0 - 4.0 | 1.0 - 8.0 | 0.5 - 2.5 mm

The base elastic floorings for use in sports, recreational and commercial facilities are often recycled rubber granules. For the recycling of these granules, the material has to pass stringent criteria of quality and environmental impact. You can rely on the cushion layers from Melos components.

90 SHORE GRANULAT

EPDM/TPE-V 90 SHORE A

Grain size 0.0 - 5.0 | 1.0 - 6.0 | 2.5 - 6.0 mm

Melos® granules with a hardness of 90 Shore A are used for special applications such as sanded floors, path and industrial floorings. The material makes it possible to create surfaces with a specified property profile and a high durability. Surfaces made of 90 Shore A granules ensure improved compressions set respectively minimal permanent deformation in a system.



High surface hardness



Are you interested in our products? Do you have any questions?

If so, get in touch with us today. We look forward to hearing from you.

Phone: +49 54 22 94 47-0 +49 54 22 59 81 Fax: Mail: info@melos-gmbh.com Follow us on social media:









Melos GmbH Bismarckstrasse 4-10 49324 Melle, Germany





